



# Prolite

Outdoor Lighting Catalogue

### Bollard Light



The 500mm (20") Bollard is complete with a spike for garden locations and lighting paths. The 1m (39") bollard is better suited for driveways and car parks. The light source, being 9w fluorescent, is both extremely efficient and gives both spread and luminescence. The lamp can be downgraded for a lesser output. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	9w PL 2G7	Warranty	10/20 years
Voltage	500mm – 12 volts	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminum.
Voltage	1m – 230-240, 110, 12 volt	Accessories	Flange, water pipe 1 ½ " S/S adaptor, inground line transformer, PIR movement detector available on 230-240v & 110v versions
Standards	AS/NZ61046, IP56, Z050,		

### Post Top Bollard Light



The 320mm (13") Bollard is designed for mounting on posts, balustrades and dividers. The light source, being 9w fluorescent, is both extremely efficient and gives both spread and luminescence. The lamp can be downgraded for a lesser output. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	9w PL 2G7	Warranty	10/20 years
Voltage	230-240, 110, 12 volt	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminum.
Standards	AS/NZ61046, IP56, Z050,	Accessories	PIR movement detector available on 230-240v & 110v versions

### Tier Light



The 500mm (20") Tier light is complete with a spike for garden situations and lighting paths. The 1m (39") tier light is better suited for driveways and car parks. The light source, being 9w fluorescent, is both extremely efficient and gives both spread and luminescence. The lamp can be downgraded for a lesser output. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	9w PL 2G7	Warranty	10/20 years
Voltage	500mm – 12 volts	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminum.
Voltage	1m – 230-240, 110, 12 volt	Accessories	Flange, water pipe 1 ½ " S/S adaptor, inground line transformer, PIR movement detector available on 230-240v & 110v versions
Standards	AS/NZ61046, IP56, Z050,		

### Branch Light



The 85mm Branch Light is specifically designed to provide uplighting in a tree, or downlighting from a tree to a garden. Fully adjustable, on a 316 Stainless Steel bracket, which is complete with a UV resistant rubber expansion strap, allowing the tree to grow.

Lamp	MR16 50w/35w/20w	Warranty	10/20 years
Voltage	12 volts	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminum.
Standards	AS/NZ61046, IP66, Z050,	Accessories	Glare guard, SP60 IP inground transformer.

### Pole Light



The 1m (39") Pole Light with 85mm (3 ½ ") head is specifically designed to provide uplighting or downlighting to a garden. Fully adjustable, 360` rotation, 180` pivot, Available as a single pole light or a twin pole light.

Lamp	MR16 50w/35w/20w	Warranty	10/20 years
Voltage	12 volts	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminum.
Standards	AS/NZ61046, IP66, Z050,	Accessories	Glare guard, SP60 IP / SP105 IP inground transformer, flange for screw mount.

### Spike Spot Light



Specifically designed to provide uplighting. Fully adjustable, 360° rotation, 180° pivot, 85mm (3 1/2") head, 300mm (12") spike.

Lamp	MR16 50w/35w/20w	Warranty	10/20 years
Voltage	12 volts	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminum.
Standards	AS/NZ61046, IP66, Z050,	Accessories	Glare guard, SP60 IP / SP105 IP inground transformer.

### Courtyard Light



Designed to provide area lighting via an adjustable (horizontal to 45° down) outward facing luminaire, plus providing up and down illumination on a building or a pillar. The inc. 105va transformer allows the user to use lamps of mixed wattage, i.e. 50w and 20w each up and down. Has more presence than the standard sized product.

Size	500mm x 127mm dia (20" x 5")	Standards	AS/NZ61046, IP66, Z050,
Lamp	MR16 50w/35w/20w	Warranty	10/20 years
Voltage	230-240v, 120v (inc. transformers), 12 volts	Material	Copper (CO), or Matt Chrome on Copper (MC)

### Down Light



Fixed fitting that provides illumination in one direction only, with 85mm (3 1/2") head

Lamp	MR16 50w/35w/20w	Warranty	10/20 years
Voltage	230-240v, 120v (inc. transformers), 12 volts	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminum.
Standards	AS/NZ61046, IP66, Z050,	Accessories	Glare guard, corrugated iron mounts (PCH), weatherboard mount (PW), SP60 IP / SP105 IP inground transformer.

### Down Light Large



Designed to provide up or down illumination on a building or a pillar. Has more presence than the standard sized product.

Size	240mm x 127mm dia (9 1/2" x 5")	Standards	AS/NZ61046, IP66, Z050,
Lamp	MR16 50w/35w/20w	Warranty	10/20 years
Voltage	230-240v, 120v (inc. transformers), 12 volts	Material	Copper (CO), or Matt Chrome on Copper (MC)

### Pillar Light



Fixed fitting that provides illumination in two directions, with 150mm (6") head

Lamp	MR16 20w x 2	Warranty	10/20 years
Voltage	230-240v, 120v (inc. transformers), 12 volts	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminum.
Standards	AS/NZ61046, IP66, Z050,	Accessories	Glare guard, corrugated iron mounts (PCH), weatherboard mount (PW), SP60 IP / SP105 IP inground transformer.



### Pillar Light Large

Designed to provide up and down illumination on a building or a pillar. Has more presence than the standard sized product.


Size	400mm x 127mm dia (16"x 5")	Standards	AS/NZ61046, IP66, Z050,
Lamp	MR16 50w/35w/20w	Warranty	10/20 years
Voltage	230-240v, 120v (inc. transformers), 12 volts	Material	Copper (CO), or Matt Chrome on Copper (MC)



### Surface Light

Surface mounted, round or square fitting with standard round, eyelid or louvre aperture flanges. The intended purpose is to illuminate steps, decks and paths.

Lamp	12v 20w burner; 12v LED; 230-240v & 120v LED; 230-240v & 120v JCDG9-25w lamp.		
Standards	AS/NZ61046, IP66, Z050,		
Warranty	10 years		
Material	Flanges -Copper, 316 Stainless Steel, Matt or Black anodised aluminium. Base - matt anodised or black anodised aluminium		



### Wall Light

The 320mm (13") wall light is intended for decks and open spaces. The light source, being 9w fluorescent, is both extremely efficient and gives both spread and luminescence. The lamp can be downgraded for a lesser output. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	9w PL 2G7	Warranty	10/20 years
Voltage	230-240, 110, 12 volt	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminium.
Standards	AS/NZ61046, IP56, Z050,	Accessories	Glare guard, corrugated iron mounts (PCH), weatherboard mount (PW), SP60, IP / SP105 IP inground transformer, PIR movement detector available on 230-240v & 110v versions



### Pillar Wall Light

The 220mm (9") pillar wall light is intended for open spaces. Can be installed either way up, with an MR16 lamp to highlight and at the other end a 20w burner lamp and diffuser for light spread.

Lamp	MR16 20w; 20w G4 burner.	Warranty	10/20 years
Voltage	230-240, 110v (inc. transformer), 12 volt	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminium.
Standards	AS/NZ61046, IP56, Z050,	Accessories	Glare guard, corrugated iron mounts (PCH), weatherboard mount (PW), SP60 IP / SP105 IP inground transformer.



### Wall Spot Light

Adjustable fitting with 85mm (3 1/2 ") head that has 350` rotation and 180` tilt. Side entry knuckle joint gives maximum flexibility, which enables angling of head to illuminate behind the fitting.

Lamp	MR16 50w/35w/20w	Warranty	10/20 years
Voltage	230-240v, 120v (inc. transformers), 12 volts	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminium.
Standards	AS/NZ61046, IP66, Z050,	Accessories	Glare guard, corrugated iron mounts (PCH), weatherboard mount (PW), SP60 IP / SP105 IP inground transformer.

### Twin Wall Spot Light



Adjustable fitting with 2 x 85mm (3 1/2") heads which have 350° rotation and 180° tilt. End entry knuckle joint. Ideal for illuminating large spaces, courtyards, driveways and decks.

Lamp	2 x MR16 50w/35w/20w	Warranty	10/20 years
Voltage	230-240v, 120v (inc. transformers), 12 volts	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminum.
Standards	AS/NZ61046, IP66, Z050,	Accessories	Glare guard, corrugated iron mounts (PCH), weatherboard mount (PW), SP60 IP / SP105 IP inground transformer, PIR movement detector available on 230-240v & 110v versions.

### Brick Light



Recessed rectangular 170mm x 80mm (6 3/4" x 3 1/4") fitting with either a protruding (portal) or flush flange. Cut out size 146mm x 62mm x 60mm (6" x 2 1/2" x 2 1/2"). The intended purpose is to illuminate steps and paths. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	12vDC LED 20,000 hour	Warranty	20 years
Current	145mA	Material	316 Stainless Steel
Standards	AS/NZ61046, IP56, Z050,	Accessories	12v DC Driver (SP LED DR or SP LED DR IP)

### Fan Light



Recessed rectangular 90mm x 110mm (3 1/2" x 4 1/2") fitting with a flush flange. Cut out size 75mm x 95mm x 60mm (3" x 3 3/4" x 2 3/8"). The intended purpose is to illuminate steps and paths. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	18 x 12vDC LED-White	Warranty	5 years
Current	138mA	Material	Epoxy resin coated Aluminium
Standards	AS/NZ61046, IP56, Z050,	Accessories	12v DC Driver (SP LED DR or SP LED DR IP)

### Deck Light



Recessed round or square 65mm (2 1/2") dia or 65mm square fitting with a flush stainless steel flange. Cut out size 53mm dia. x 50mm deep (2"x2"). The intended purpose is to provide border lighting in paths and decks, and can be used as step lights in vertical walls. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	12 x 12vDC LED- White, Blue/Red (specify colour)	Warranty	5 years
Current	75mA	Material	316 Stainless Steel flange / Epoxy resin filled polymeric housing.
Standards	AS/NZ61046, IP65, Z050,	Accessories	12v DC Driver (SP LED DR or SP LED DR IP)

### Step Light / Floor Light



Recessed round (100mm dia. - 4") or square (100mm x 100mm - 4" x 4") fitting with standard round, eyelid or louvre aperture flanges. The intended purpose is to illuminate steps, decks and paths. Flanges available with mounting screw holes (cutout 65mm dia. x 100mm deep - 2 1/2" x 4") or smooth finish for use in conjunction with concrete placement cans.

Lamp	12v MR16 20w ; 12v LED; 230-240v & 120v LED.	Material	Copper, 316 Stainless Steel, Matt or Black anodised aluminum.
Standards	AS/NZ61046, IP66, Z050,	Accessories	Concrete placement can (PCAN) - 75mm x 150mm (3" x 6").
Warranty	10/20 years		



### Flush Floor Light

Recessed round (76mm dia. x 100mm deep – 3” x 4”) fitting with LED lamp and frosted lens, complete with copper rimmed can. The fitting is designed to be totally flush with the floor. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp and can be walked on.

Lamp	12v MR16 LED	Warranty	20 years
Standards	AS/NZ61046, IP66, Z050,	Material	Copper.



### Pond Light

Specifically designed to be submerged and provide uplighting. Fully adjustable, 360° rotation, 180° pivot, 85mm (3 1/2”) head, complete with weighted base and 5m of flex.

Lamp	MR16 50w/35w/20w	Warranty	20 years
Voltage	12 volts	Material	Copper, 316 Stainless Steel.
Standards	AS/NZ61046, IP68, Z050,	Accessories	Glare guard, SP60 IP / SP105 IP inground transformer.



### Pool Light

Specifically designed to be submerged and recessed into ponds and pools. Complete with a Canister and 4m of 3 core flex. Note: this unit must be earthed for swimming pools

Lamp	MR16 50w/35w/20w	Warranty	20 years
Voltage	12 volts	Material	Electro Polished 316 Stainless Steel
Standards	AS/NZ61046, IP68, Z050,		



### Inground Up Light

Recessed round (270mm flange – 10 1/2”) or square (270mm x 270mm -10 1/2” x 10 1/2”) fitting with a flush stainless steel flange. Cut out size 210mm dia. x 250mm deep (8”x10”). Designed to provide uplighting for buildings, tall trees, etc. Indicative illumination area 20m (66ft) high x 10m (33ft) spread. Adjustable reflector, vertical to 68°, 360° rotate, can be driven over. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	26w ES CFL	Warranty	20 years
Voltage	230 – 240v, 120v	Material	316 Stainless Steel
Standards	AS/NZ61046, IP66, Z050,	Accessories	Frosted lens



Available  
Sept 08'

### Lawn Light

Recessed fitting specifically designed to provide uplighting from a ground situation. Fully adjustable -360° rotation, 22° pivot from vertical. 140mm (5 1/2”) dia. flange x 120mm (4 3/4”) deep

Lamp	MR16 50w/35w/20w	Warranty	10 years
Voltage	12 volts	Material	Matt anodised aluminum.
Standards	AS/NZ61046, IP66, Z050,	Accessories	SP60 IP / SP105 IP inground transformer.



### Path Light

Recessed fitting specifically designed to provide surround lighting from the ground situation. 100mm (4") dia. flange, 63mm x 100mm (2 1/2" x 4") barrel. Canister required. Available with single (120°) or twin facet (270°). Inc. LED driver. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	4 x LED; 8 x LED	Warranty	20 years
Voltage	12 volts	Material	Bronze
Standards	AS/NZ61046, IP66, Z050,	Accessories	Canister (PCAN)



### Pigmy Spike Spot

Smaller profile light designed to provide discreet lighting. Incorporating energy efficient PCB and energy efficient light emitting diodes (LED). Fully adjustable, 360° rotation, 180° pivot, 50mm x 25mm dia. (2" x 1") head, 300mm (12") spike. Standard lens is 12° spot, 90° flood lens available on request. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	LED 3w	Warranty	20 years
Voltage	12 volt DC	Material	Copper
Standards	AS/NZ61046, IP66, Z050,	Accessories	SP LED DR or SP LED DR IP drivers



### Pigmy Down Light

Smaller profile light designed to provide discreet lighting. Incorporating energy efficient PCB and energy efficient light emitting diodes (LED). Fixed wall light, one direction only. 50mm x 25mm dia. (2" x 1") head. Standard lens is 12° spot, 90° flood lens available on request. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	LED 3w	Warranty	20 years
Voltage	12 volt DC	Material	Copper
Standards	AS/NZ61046, IP66, Z050,	Accessories	SP LED DR or SP LED DR IP drivers



### Pigmy Pillar Light

Smaller profile light designed to provide discreet lighting. Incorporating energy efficient PCB and energy efficient light emitting diodes (LED). Fixed wall light, two directions only. 100mm x 25mm dia. (4" x 1") head. Standard lens is 12° spot, 90° flood lens available on request. This fixture remains cool to the touch, is energy efficient and comes with a long life lamp.

Lamp	2 x LED 3w	Warranty	20 years
Voltage	12 volt DC	Material	Copper
Standards	AS/NZ61046, IP66, Z050	Accessories	SP LED DR or SP LED DR IP drivers

## FEATURES

- » 20 year warranty (excluding consumables – lamps, lamp holders, transformers) on 316 Stainless Steel and solid Copper.
- » 10 year warranty (excluding consumables - lamps, lamp holders, transformers) on Black or Matt Anodised Aluminium.
- » 1 year warranty SP transformers.
- » Energy efficiency prerogatives followed.
- » Unique lens making for clean looking appearance
- » Flush lens, patented.
- » Hidden screw fixings.
- » Products are waterproof (following guidelines).
- » Lamp chambers will not wick moisture.
- » All products are resistant to salt and will not peel.
- » Designed and manufactured in New Zealand.
- » Easily replaced lamps/bulbs.
- » All products are accurate at the time of print, but subject to change

(Cover picture: Petone Wharf, Wellington, New Zealand, PL18 watt Prolite bulkheads [www.prolitemarine.com](http://www.prolitemarine.com))

## DISTRIBUTION AND SALES

### **Prolite UK**

[sales@prolite.biz](mailto:sales@prolite.biz)

[www.prolite.biz](http://www.prolite.biz)

### **Prolite Australia**

[sales@salepro.co.nz](mailto:sales@salepro.co.nz)

[www.prolite.co.nz](http://www.prolite.co.nz)

### **Prolite USA**

[sales@salepro.com](mailto:sales@salepro.com)

[www.salepro.com](http://www.salepro.com)

### **Prolite New Zealand**

(Corporate Office / Factory)

Salepro Ltd.

73 Taylor St

Carterton, NZ

[sales@salepro.co.nz](mailto:sales@salepro.co.nz)

[www.prolite.co.nz](http://www.prolite.co.nz)

Ph +64/ 6-379-8402

Fax +64/ 6-379-8496

